

HFX SERIES Ø 415-960



HFX SERIES BED HEIGHT 500-600


Manufactured and calculated according to EN 13121-3.
 Material: Hand lay-up polyester with fiberglass (max quality polyester tech).
 Steel reinforced GRP vessel.
 All threaded connections are part of the structure of the filter in GRP.
 Closed legs & part of the filter structure.
 Top access.
 Design temperature 40°C.
 Laterals distribution.
 Top distributor according to the media/application.
 Tested 1.5 times design pressure

ADDITIONAL OPTIONS

Higher temperatures.
 High-chemical resistance.
 Flange connections available in HFX
 Anchorage system to ground.
 Seismic calculations.
 Drinking water / Food contact.
BESGO READY FILTERS

WHY HFX SERIES?

HFX SERIES includes a bit higher bed depth than FA filters and a sightglass (very important to check backwash performance and top part of the filtering media).



Integrated GRP threads

Metallic top lid

Sight glass

Arms collector

Diffuser for Sand / AFM

Emptying plug

Besgo ready

Design pressure: 2.5 / 5 / 7 bars

	FA-6	FA-8	FA-10	FA-15	FA-20	FA-30	FA-35
D	415	460	520	640	720	840	960
H	821	821	891	946	1065	1125	1135
A	260	260	310	310	360	360	360
B	190	190	190	190	190	190	250
I/O	2"	2"	2"	2"	2"	2"	2 1/2"
Emptying	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Top air relief	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Filt. Surface	0.13m ²	0.16m ²	0.20m ²	0.30m ²	0.40m ²	0.52m ²	0.70m ²